



BALER TWINE PRODUCT SELECTION GUIDE

C O R D A G E

SMALL SQUARE	Minimum Knot Strength	Guaranteed Ft/ Carton	Spools/ Carton	Cartons/ Pallet	Description
9,000'—130	130	9,000'	2	50	Used in 14" x 18" balers (up to 75 lb. bales)
9,000'—130 Single Spool	130	9,000'	1	60	Used in 14" x 18" balers, less changeover time
7,200'—170	170	7,200'	2	50	Heavy-duty twine for 14" x 18" balers
7,200'—190 Single Spool	190	7,200'	1	60	Heavy-duty twine for 14" x 18" balers, less changeover time
9,600'—170	170	9,600'	2	40	Light-duty twine for 16" x 18" balers (up to 100 lb. bales)
9,600'—210 XSR®	210	9,600'	2	40	Extra, shock-resistant twine for 16" x 18" balers
WIRE REPLACEMENT					
5,000'—210	210	5,000'	1	80	Heavy-duty twine for 16" x 18" balers
6,500'—210	210	6,500'	1	48	Heavy-duty twine for 16" x 18" balers
6,500'—240	240	6,500'	1	48	For 2- and 3-tie balers
8,500'—245	245	8,500'	1	48	For 3-tie balers with extra footage
7,400'—250	250	7,400'	1	48	Medium-duty for 3-tie balers, plus extra footage
7,000'—280	280	7,000'	1	48	Super-heavy-duty for 3-tie balers, plus extra footage
9,400'—Showdown® 3-tie	3-tie	9,400'	1	48	Longer length twine for 3-tie balers for retail hay applications
LARGE SQUARE					
4,000'—350 No Box	350	4,000'	1	48	For 3' x 3', 3' x 4' and 4' x 4' balers
4,850'—350 No Box	350	4,850'	1	48	Extra footage for 3' x 3', 3' x 4' and 4' x 4' balers
4,000'—400 No Box	400	4,000'	1	48	Medium-duty for 3' x 3', 3' x 4' and 4' x 4' balers
4,750'—400 No Box	400	4,750'	1	48	Medium-duty for 3' x 3', 3' x 4' and 4' x 4' balers, plus extra footage
4,000'—440 No Box	440	4,000'	1	48	Heavy-duty for 3' x 3', 3' x 4' and 4' x 4' balers
4,000'—450 No Box	450	4,000'	1	48	Heavy-duty for 3' x 3', 3' x 4' and 4' x 4' balers
4,000'—500 No Box	500	4,000'	1	36	Super-heavy-duty for 3' x 3', 3' x 4' and 4' x 4' baler
3,540'—Bridon HD™ 1	HIGH DENSITY	3,450'	1	48	Maximum duty for new-generation, high-density balers
LARGE SQUARE - SUPER LONG LENGTH					
6,200'—350 Endurance®	350	6,200'	1	48	Maximum footage for new-generation big square balers
5,830'—400 Endurance®	400	5,830'	1	48	Maximum footage for new-generation big square balers, medium duty
5,050'—450 Endurance®	450	5,050'	1	48	Maximum footage for new-generation big square balers, heavy duty
ROUND - SLIT FILM					
	Average Tensile Strength	Guaranteed Ft/ Carton	Spools/ Carton	Cartons/ Pallet	Description
20,000'—110 Ultima®	110	20,000'	2	50	Economical light-duty twine
20,000'—110 Single No Box	110	20,000'	1	80	Economical light-duty twine; less changeover time
20,000'—110 Eclipse® No Box	110	20,000'	1	80	Photodegradable, economical light-duty
28,000'—110 Banded	110	28,000'	2	50	Economical light-duty twine; extra footage for longer baling intervals
40,000'—110 Banded	110	40,000'	2	40	Economical light-duty twine; extra footage for longer baling intervals
20,000'—130 Ultima®	130	20,000'	2	50	Most popular and widely used
20,000'—150 Ultima® II	150	20,000'	2	50	Heavy-duty twine
ROUND - MONOFILAMENT					
20,000'—110 Sidewinder™ Single	110	20,000'	1	80	High-visibility
20,000'—110 Stinger™	110	20,000'	2	50	High-visibility
28,000'—110	110	28,000'	2	40	High-visibility, plus extra footage
20,000'—130 TNT®	130	20,000'	2	50	High-visibility (blue/yellow)
28,000'—130 TNT®+	130	28,000'	2	40	High-visibility, plus extra footage
20,000'—140 Stinger™	140	20,000'	2	50	High-visibility